

## SUBSEA SAW 60 – 200 MM



The IKM Subsea manipulator held **Subsea Saw** has a long track record. It is designed to cut steel pipes, profiles, chains, armored cables and flexible riser up to 200 mm. The saw has a clamp and an automatic feed function on the sawblade.

### SPECIFICATIONS

|  |   |
|--|---|
| <b>Type</b>                            | Subsea Saw  |
| <b>Model</b>                           | 60 – 200 mm   |
| <b>Part number</b>                     | IKM-1047718   |
| <b>Dimensions LxWxH</b>                | 1455 x 716 x 423 mm   |
| <b>Cutting diameter</b>                | Ø60 – Ø200  |
| <b>Saw blade</b>                       | Ø600  |
| <b>Motor</b>                           | 305 cc  |
| <b>Recommended feed rate</b>           | 15–25 mm/min  |
| <b>Hydraulic Connections</b>           | 2x ½" BSP (HF)<br>2x ¼" BSP (LF)  |
| <b>Hydraulic pressure</b>              | 180-200 bar   |
| <b>Hydraulic flow</b>                  | 55-65 LPM   |
| <b>Weight in air</b>                   | 89 kg   |
| <b>Weight in water</b>                 | 68 kg   |
| <b>Number of hydraulic connections</b> | 4 hoses<br>(two functions)<br><br>HF: Minimum NG6 Valve<br>LF: NG4 or NG3 Valve |

- Claws can be modified to different interfaces and diameters if required.
- Standard blades supplied with the saw are Ø600 carbide and diamond types.
- HF: Minimum NG6 Valve
- LF: NG4 or NG3 Valve